

Peterson Europe Standing out from the crowd...

EXCEPTIONAL QUALITY FROM A BRAND YOU CAN TRUST

1350 lumens measured output Integral Deutsch connector Optional handle and/or manual control switch Flood pattern Multi-voltage: 10-30Vdc 100 x 100mm square design Aluminium die cast housing, black E-coat finish Polycarbonate lens Stainless steel mounting Certified to ECE Reg 10

Standard PM-910 work light without DT connector also available

PM-910 DT series LED work light with integral Deutsch connector










DATA SHEET

PM-910 DT series LED work light with integral Deutsch connector






Image shown with optional handle and manual control switch





Dimensions





Drawing shown with optional handle and manual control switch

Specifications Functions: LED work

Functions:	LED work light with Deutsch connector and optional handle and/or manual control switch
LEDs:	9 x high brightness white diodes
Output:	1350 lumens
Light pattern:	Flood light pattern
Certifications:	ECE Reg 10: E50-10R-050067
Dimensions:	100 x 100mm square design
Voltage:	Muli-voltage
Operating range:	10-30Vdc
IP rating:	IP69K
Operating temperature:	-40°C to +65°C
Mounting:	U-bracket with M10x25mm bolt, nut and washer
Cables & Wiring:	Integral DT compatible receptacle Supplied with mating DT connector and 18 AWG cable, 50cm long (+/-5cm) Red wire = power Black wire = ground
Current draw:	1.2A @ 13.5V / 0.6A @ 28V
Reverse polarity protection:	Yes
Warranty:	3 years

Materials

Lens:	Polycarbonate
Housing:	Die cast aluminium, black E-coat finish
Handle:	Die cast
Mounting:	Stainless steel

Part numbers

PM-910-MV-DT	LED work light with integral DT connector
PM-910S-MV-DT	LED work light with integral DT connector and switch
PM-910SH-MV-DT	LED work light with integral DT connector, switch & handle

Standard PM-910-MV work light without DT connector also available

 (\mathfrak{A})