

DATA SHEET

PM-1216/1217/1218R-9

LED Rear position & Stop Light



Images

LumenX




Rear of light showing built-in AMP compatible receptacle & plug




PM-B426-18 grommet




Dimensions




Surface mount with bracket




PM-1217R-9 light module



Flange mount



PM-B426-18 grommet



Specifications

Functions:	LED rear position & stop light
LEDs:	9 x LEDs
Lens type:	LumenX®
Lens colour:	Red
Certifications:	ECE Reg 7
Voltage:	Dual voltage 12/24Vdc
IP rating:	IP67
Operating temperature:	-30°C to +50°C
Mounting:	PM-1216R & 1216RC surface mount with bracket PM-1217R-9 surface mounts using a PM-B817 series bracket or flush mounts using PM-B426-18 grommet PM-1218R-9 flange mounts
Wiring:	Built-in AMP-compatible receptacle for direct attachment to body harness, or requires PM-B417-49 or PM-B817-49 plug
Power rating:	6.0W @ 12V / 6.0W @ 24V
Average current draw:	Position 0.02A @ 12V / 0.06A @ 24V Stop 0.17A @ 12V / 0.29A @ 24V
Reverse polarity protection:	Yes
Warranty:	3 years



Materials

Lens:	PMMA-HI
Base:	ABS

Part numbers

PM-1216R-9	LED position & stop light- surface mount, black bracket
PM-1216RC-9	LED position & stop light - surface mount, chrome bracket
PM-1217R-9	LED position & stop light module - (see mounting accessories below)
PM-1218R-9	LED position & stop light- flange mount
PM-B817-09	Black bracket for PM-1217F-9 (surface mounting)
PM-B817-10	Chrome bracket for PM-1217F-9 (surface mounting)
PM-B426-18	Grommet for PM-1217F-9 (flush mounting)
PM-B417-49	3 wire plug
PM-B817-49	3 wire plug (moulded)

+44 (0) 1296 340045

sales@petersonseurope.co.uk
sales@petersonseurope.eu

petersonseurope.com
petersonseurope.eu

