

DATA SHEET

PM-710C

90mm LED combination headlight




Images



Specifications

Functions:	Combination low and high beam Left-hand and right-hand traffic variants
LEDs:	1 diode for low beam, 2 diodes for high beam module
Certifications:	ECE Reg 10 ECE Reg 112 Class B: E6-112R-010872 - left-hand traffic version E6-112R-010871 - right-hand traffic version
Voltage:	Multi-voltage 9-32Vdc
IP rating:	IP68
Operating temperature:	-30°C to +65°C
Mounting:	Industry standard 4-point mounting with 85mm centres
Wiring:	40cm long co-extruded Red = high beam White = low beam Black = ground
Power rating:	22W@12V / 20W@24V (low beam) 28W@12V / 33W@24V (high beam)
Reverse polarity protection:	Yes
Warranty:	3 years


Dimensions




Materials

Outer lens:	Polycarbonate, clear, hard coated
Inner lens:	PMMA
Housing:	Aluminium, black E-coat finish
Front/rear covers	Polycarbonate, black

Illuminance on road surface: low beam
(LHT beam pattern shown)



Illuminance on road surface: high beam



Part numbers

PM-710C-ECE-LHT	Combination low/high beam, left-hand traffic
PM-710C-ECE-RHT	Combination low/high beam right-hand traffic

+44 (0) 1296 340045

sales@peterson europe.co.uk
sales@peterson europe.eu

peterson europe.com
peterson europe.eu

