

Peterson Europe

Vehicle lighting solutions
by design, by technology, by quality

EXCEPTIONAL QUALITY FROM A BRAND YOU CAN TRUST



A high power LEDs
Class-beating light output
Certified to ECE R65: amber only
Certified to ECE R10
Dual voltage 12/24V
Multiple selectable flash patterns
Multiple units can be synchronised
Surface mount
Available in amber (R65), red and blue
Aluminium die cast housing
Dimensions: 73 x 55 x 14mm
IP69K rated

SL-1047X series
LED directional warning light



















DATA SHEET

SL-1047X Series

LED directional warning light











Images











Specifications

Functions: LED directional warning light

LEDs: 4 x high power LEDs

Multiple selectable flash patterns Flash patterns & Multiple units can be synchronised sychronisation:

Certifications: ECE Reg 10-05 16505

ECE Reg 65: XA100 6401 (amber only)

Dimensions: 73 x 55 x 14mm

> Voltage: Dual voltage 12/24V

IP rating: IP69K

Operating -30°C to +50°C temperature:

Mounting: Surface mount

> Wiring: Red = power

Black = ground

Green = flash pattern selection & sychronising

White = alternate flash

Power rating:

Amber: 0.75A @ 13.5Vdc / 0.38A @ 28Vdc Current draw:

0.64A @ 13.5Vdc / 0.35A @ 28Vdc 0.76A @ 13.5Vdc / 0.40A @ 28Vdc Blue:

Reverse polarity

Yes protection:

Warranty: 3 years



Materials

Lens: Polycarbonate

Housing: Aluminium die cast

Part numbers

SL-10471	Surface mount LED directional warning light, R65 - amber
SL-10472	Surface mount LED directional warning light - red
SL-10473	Surface mount LED directional warning light - blue









